

## Instruction

With an Android operating system, DNAKE 902M-S8 provides high-definition audio and video communication with Door Station and indoor monitor via SIP 2.0 protocol. It also allows integration with 3rd party application and elevator control system, offering an integrated security solution.

## DNAKE 902M-S8



## Key Features

- Android System
- 7-inch capacitive touch screen
- Powered by PoE or power adapter (DC12V/2A)
- Support SIP 2.0 protocol, easy integration with other SIP devices
- Compatible with 3rd party application
- Easy integration with elevator control system
- Support monitoring 8 IP cameras

## Physical

- System: Android
- RAM: 1 GB
- ROM: 4 GB
- Front Panel: Plastic
- Power Supply: PoE (802.3af) or DC 12V/2A
- Standby Power: 3 W
- Rated Power: 10 W
- Wi-Fi: IEEE802.11 b/g/n, @2.4GHz (Optional)
- Camera: 0.3MP, CMOS (Optional)
- TF Card Port: 1
- USB Port: 1
- Ethernet Port: 1 x RJ45, 10/100 Mbps adaptive
- RS485: 1
- Power Output: 1 (12V/100mA)
- Doorbell Input: 8 (use any alarm input port)
- Alarm Input: 8
- Installation: Surface Mounting
- Dimension: 221.4 x 151.4 x 16.5 mm
- Working Temperature: -10°C to +55°C
- Storage Temperature: -40°C to +70°C
- Working Humidity: 10% to 90% (non-condensing)



# Datasheet

## Display

- Display: 7-inch TFT LCD
- Screen: Capacitive touch screen
- Resolution: 1024 x 600

## Audio

- Audio Codec: G.711
- Echo Cancellation
- DTMF: RFC2833
- Microphone: Built-in microphone
- Speaker: Built-in speaker

## Video

- Video Codec: H.264

## Networking

- Protocol: SIP, UDP, TCP, RTP, RTSP, NTP, DNS, HTTP, DHCP, IPV4, ARP, ICMP

## Package Features

- Package Content:
  - DNAKE 902M-S8  
(Power adapter not included)
  - Bracket
  - Screwing Kit
  - Quick Start Guide
- Qty/CTN: 20 pcs
- N.W/PCS: 0.51 kg
- G.W/CTN: 15.82 kg
- Giftbox Size: 310 x 216 x 68 mm
- Carton Size: 360 x 640 x 460 mm

