

DNAKE C-series Linux Door Station Release

Notes of Version 3.2

1. Introduction

In this update, we have supported and improved more than 30 functions, especially the connection and communication with DNAKE cloud, and support for simultaneous registration of two SIP accounts, which greatly meets the application needs of customers.

- Firmware Version: 170SD_1_3_2_12_GA_20251229 or above
- Applicable Model:

C112

2. New Features

- Supports configuration of whether to connect to DNAKE cloud
- Support registering two SIP accounts
- Support configuring different accounts for contacts
- Support switching Relay on WebUI
- DHCP is enabled by default
- Support full card number reading
- Supports configuration of external Wiegand
- Support configuring different card readers to open different relays
- Support triggering unlocking and calling after DCI input signal
- Supports unlocking via HTTP commands

- Support configuring Web Relay Action in WebUI
- WebUI supports Japanese, Russian, and Ukrainian
- Supports call transfer and simultaneous ringing through Ring Group functionality.
- Supports configuration of voice broadcast IP addresses.

3. Optimization

- Improved Concierge configuration function
- Improved WebUI contact list experience
- Enhance the user experience of the management cards
- Improve WebUI menus and configuration items
- Optimize the playback experience of IP addresses
- Optimize and improve the call and connection experience with DNAKE Cloud
- Improved the person functionality in the WebUI to support the creation of person roles

4. Bug Fixes.

- Fix some bugs