

## DNAKE DK250



### Instruction

DNAKE wireless video doorbell systems operate in 2.4GHz communication. Any door camera can come with one or two Indoor Monitor. The system is easy to install and usually don't require any additional costs, and has a long-range transmission.

### Key Features

- Plug and Play
- Long-range transmission (400m in open area)
- One door camera supports two indoor monitors
- One indoor monitor supports 2 door cameras
- Multi-languages (English, Nederlands, Polski, Deutsch, Français, Italiano, Español, Português, Русский, Türk)



## Door Camera Physical

- Panel: Plastic
- Color: Silver
- Flash: 64 MB
- Button: Mechanical
- Dimension: 160 x 86 x 55 mm
- Installation: Surface mounting
- Power: DC 12V or 2\*Battery (C size)
- IP Rating: IP65
- LED: 6 pcs
- Camera: 0.3 MP
- Video Resolution: 640 x 480
- Viewing Angle: 105°
- Audio Codec: G.711a
- Video Codec: H.264
- Transmit Frequency Range: 2.4GHz-2.4835GHz
- Data Rate: 2.0 Mbps
- Modulation Type: GFSK
- Transmit Distance (in open area): 400 m
- Working Temperature: -10°C to +55°C
- Storage Temperature: -10°C to +70°C
- Working Humidity: 10% to 90% (non-condensing)

## Indoor Monitor Physical

- Panel: Plastic
- Color: Silver/Black
- Flash: 64 MB
- Button: 9 Touch Buttons
- Dimension: 214.85 x 149.85 x 21 mm
- Screen: 7-inch TFT LCD
- Resolution: 800 x 480
- Installation: Surface mounting or Desktop
- Power: Rechargeable Lithium Battery (2500mAh)
- Snapshot: 75 pcs
- Video Recording: Yes
- TF Card : 32G
- Audio Codec: G.711a
- Video Codec: H.264
- Multi-languages: 10
- Transmit Frequency Range: 2.4GHz-2.4835GHz
- Data Rate: 2.0 Mbps
- Modulation Type: GFSK
- Transmit Distance (in open area): 400 m
- Working Temperature: -10°C to +55°C
- Storage Temperature: -10°C to +70°C
- Working Humidity: 10% to 90% (non-condensing)

