

Datasheet

Instruction

The DNAKE E217 provides multiple functions, including audio and video intercom, emergency call, security alarm, and lift control, etc. It also supports communication via SIP 2.0 protocol with IP phones and IP-PBX. It allows the constructor to make an easy configuration and installation.

DNAKE E217



Key Features

- 7-inch capacitive touch screen
- Powered by PoE or power adapter (DC12V/2A)
- Optional dual network ports
- Optional Support Wi-Fi
- Support monitoring 16 IP cameras
- Support TF card

Physical

- System: Linux
- RAM: 128 MB
- ROM: 128 MB
- Front Panel: Plastic
- Power Supply: PoE (802.3af) or DC 12V/2A
- Standby Power: 2 W
- Rated Power: 9 W
- Wi-Fi: IEEE802.11 b/g/n,@2.4GHz
- Ethernet Port: 1 x RJ45, 10/100 Mbps adaptive
- TF Card Slot: 1
- RS485: 1
- Power Output: 1 (12V/100mA)
- Doorbell Input: 8 (use any alarm input port)
- Alarm Input: 8
- Installation: Surface Mounting / Desktop
- Dimension: 195 x 130 x 14.5 mm
- Dimension (Easy-to-Install Back Cover): 195 x 130 x 21 mm
- Working Temperature: -10°C to +55°C
- Storage Temperature: -40°C to +70°C
- Working Humidity: 10% to 90% (non-condensing)



Datasheet

Display

- Display: 7-inch TFT LCD
- Screen: Capacitive touch screen
- Resolution: 1024 x 600

Audio

- Audio Codec: G.711
- Echo Cancellation
- DTMF: RFC2833
- Microphone: Built-in microphone
- Speaker: 8Ω / 1W

Video

- Video Codec: H.264

Networking

- Protocol: SIP, UDP, TCP, RTP, RTSP, NTP, DNS, HTTP, DHCP, IPV4, ARP, ICMP

Package Features

- Package Content:
 - DNAKE E217
(Power adapter not included)
 - Bracket
 - Screwing Kit
 - Quick Start Guide
- Qty/CTN: 22 pcs
- N.W/PCS: 0.47 kg
- G.W/CTN: 12.70 kg
- Giftbox Size: 236 x 157 x 45 mm
- Carton Size: 535 x 500 x 170 mm

