

# Datasheet

## DNAKE IPK06



### Instruction

Embrace security with a simple touch. DNAKE IP Video Intercom kit is a complete solution that includes a door station, an indoor monitor, and accessories to mount. New IP intercom kit is immediately ready for use and does not require any special programming. Improve your safety at home while increasing convenience with DNAKE IP Video Intercom Kit!

### Key Features

- Plug & Play
- User-friendly interface
- Standard PoE
- IK07 & IP65
- Multiple Unlock methods (Card, PIN Code, Temp Key, QR Code, APP, Indoor monitor)
- Check alarm notifications on the APP
- CCTV integration
- Extendable to 2 Door stations, 6 indoor Monitors

### Package Features

- Package Content:
  - E217 (KIT) + S213K (KIT)
  - Brackets: 2 pcs (indoor monitor and door station)
  - Screwing Kit
  - User Manual
- Qty/CTN: 9 pcs
- N.W/PCS: 1.25 kg
- G.W/CTN: 14.55 kg
- Giftbox Size: 280 x 235 x 65 mm
- Carton Size: 660 x 330 x 280 mm



# Datasheet


## Key Features

- 7-inch capacitive touch screen
- Powered by PoE or DC12V
- Support SIP 2.0 protocol, easy integration with other SIP devices
- Support monitoring 8 IP cameras
- Support TF card

## Physical

- Front Panel: Plastic
- System: Linux
- RAM: 128 MB
- ROM: 128 MB
- Power Supply: PoE (802.3af) or DC 12V/2A
- Standby Power: 2 W
- Rated Power: 9 W
- Ethernet Port: 1 x RJ45, 10/100 Mbps adaptive
- TF Card Slot: 1
- RS485: 1
- Power Output: 1 (12V/100mA)
- Doorbell Input: 8 (use any alarm input port)
- Alarm Input: 8
- Installation: Surface Mounting / Desktop
- Dimension: 195 x 130 x 21mm
- Working Temperature: -10°C to +55°C
- Storage Temperature: -40°C to +70°C
- Working Humidity: 10% to 90% (non-condensing)

## DNAKE E217 (KIT)



## Display

- Display: 7-inch TFT LCD
- Screen: Capacitive touch screen
- Resolution: 1024 x 600

## Audio

- Audio Codec: G.711
- Echo Cancellation
- DTMF: RFC2833
- Microphone: Built-in microphone
- Speaker: 8Ω / 1W

## Video

- Video Codec: H.264

## Networking

- Protocol: SIP, UDP, TCP, RTP, RTSP, NTP, DNS, HTTP, DHCP, IPV4, ARP, ICMP



# Datasheet

## Key Features

- Powered by PoE or power adapter (DC12V/2A)
- Support IC Card (13.56MHz) & ID Card (125kHz), PIN Code, Temp Key, QR Code
- 3 Indicator Lights
- 2 relays supported
- Tamper alarm

## DNAKE S213K (KIT)



## Physical

- Front Panel: Aluminum
- System: Linux
- RAM: 64 MB
- ROM: 128 MB
- Power Supply: PoE (802.3af) or DC 12V/2A
- Standby Power: 1.5 W
- Rated Power: 3.5 W
- Camera: 2MP, CMOS
- Indicator Light: 3
- Wiegand Port: Support
- Ethernet Port: 1 x RJ45, 10/100 Mbps adaptive
- Door Entry: IC Card(13.56MHz) & ID Card (125kHz), PIN Code, Temp Key, QR Code
- Reset Button: 1
- RS485 Port: 1
- Relay Out: 2
- Input: 2
- IP / IK Rating: IP65 / IK07
- Multiple Installations: Surface Mounting(Default Bracket), Flush Mounting(Optional)
- Surface Mounting DIM:
  - Bracket: 188 x 88 x 34 mm
  - Aluminum Rain Hood (RH08): 193.5 x 94 x 53 mm
  - Aluminum Rain Hood (RH09): 194 x 94 x 66 mm
  - Stainless Rain Hood (RH13): 193 x 89 x 64.5 mm
  - Stainless Rain Hood(RH01): 179 x 92.8 x 50.5 mm
- Flush Mounting DIM: 120 × 230 × 48 mm
- Working Temperature: -40°C to +55°C
- Storage Temperature: -40°C to +70°C
- Working Humidity: 10% to 90% (non-condensing)



# Datasheet

## Audio

- Audio Codec: G.711
- Echo Cancellation
- DTMF: RFC2833
- Microphone: Built-in microphone
- Speaker: Built-in speaker

## Networking

- Protocol: ONVIF, SIP, UDP, TCP, RTP, RTSP, NTP, DNS, HTTP, DHCP, IPV4, ARP, ICMP

## Video

- Video Codec: H.264
- Video Resolution: 1280 x 720
- Viewing Angle: 110°(H) / 60°(V) / 125°(D)
- Max. Image Transfer Rate: 720p – 25fps
- Light Compensation: LED white light

