Datasheet

Instruction

DNAKE N1146

The DNAKE N1146 provides multiple functions, including audio and video intercom, emergency call, security alarm and lift control, etc. It also supports communication via SIP 2.0 protocol with IP phone and IP-PBX. It allows constructor to make an easy configuration and installation.



Key Features

- Easy configuration
- 7-inch capacitive touch screen
- Powered by PoE or power adapter (DC12V/2A)
- Support SIP 2.0 protocol, easy integration with other SIP devices
- Easy integration with elevator control system

Physical

- System: Linux
- RAM: 64 MB
- ROM: 128 MB
- Front Panel: Plastic
- Power Supply: PoE (802.3af)or DC 12V/2A
- Ethernet Port: 1 x RJ45, 10/100 Mbps adaptive
- Power Output: 1 (12V/100mA)
- Alarm Input: 8
- Installation: Surface Mounting
- Dimension: 177.5 x 111.2 x 14 mm
- Working Temperature: -10℃ to +55℃
- Storage Temperature: -40℃ to +70℃
- Working Humidity: 10% to 90% (non-condensing)

Datasheet

Display

- Display: 7-inch TFT LCD
- Screen: Capacitive touch screen
- Resolution: 1024 x 600

Audio

- Microphone: Built-in microphone
- Speaker: 8Ω / 1W

Video

- Video Codec: H.264

Networking

- Protocol: SIP, UDP, TCP, RTP, RTSP, NTP, DNS, HTTP, DHCP, IPV4, ARP, ICMP