

Datasheet

Instruction

DNAKE S617 provides an integrated security solution. It enables user to open the door by facial recognition with liveness detection, IC & ID card and PIN Code. It also makes an easy video call with indoor monitor and mobile APP, to achieve a convenient and secure life.

Key Features

- 8-inch IPS LCD capacitive touch screen
- 3 output relays for door locks
- 120° wide-angle 2MP HD camera with automatic lighting
- Support WDR technology to lighten the dark areas and darken the overexposed parts of the image
- Support 20,000 users, 20,000 faces, and 60,000 cards
- Tamper alarm

Physical

- System: Android
- RAM: 2 GB
- ROM: 8 GB
- Front Panel: Aluminum
- Power Supply: PoE+ (802.3at) or DC 12V/3A
- Standby Power: 8 W
- Rated Power: 16 W
- Camera: 2MP, CMOS, WDR
- IR Sensor: Support
- Wiegand Port: Support
- Ethernet Port: 1 x RJ45, 10/100 Mbps adaptive
- Door Entry: Face, IC (13.56MHz) & ID (125kHz) card, PIN code, Bluetooth
- MIFARE Plus SL1/SL3 Card: Support
- Reset Button: 1
- RS485 Port: 1
- Relay Out: 3
- Input: 4
- IP / IK Rating: IP65 / IK08
- Installation: Surface Mounting
- Surface Mounting DIM: Surface Box: 300 x 140 x 41.8 mm
- Aluminum Rain Hood RH15: 308.1 x 145 x 80.92 mm
- Working Temperature: -40°C to +55°C
- Storage Temperature: -40°C to +70°C
- Working Humidity: 10% to 90% (non-condensing)

DNAKE S617

(Surface Mounting)



Datasheet

Display

- Display: 8-inch IPS LCD
- Resolution: 1280 x 800

Audio

- Audio Codec: G.711
- Echo Cancellation
- DTMF: RFC2833
- Microphone: Built-in microphone
- Speaker: 8Ω / 1W

Video

- Video Codec: H.264
- Video Resolution: up to 1920 x 1080
- Viewing Angle: 120°(H) / 75°(V) / 131°(D)
- Max. Image Transfer Rate: 1080p – 25fps
- Light Compensation: LED white light

Networking

- Protocol: ONVIF, SIP, UDP, TCP, RTP, RTSP, NTP, DNS, HTTP, DHCP, IPV4, ARP, ICMP

Package Features

- Package Content:
 - DNAKE S617/S
(Power adapter not included)
 - Surface Mounting Box
 - Hanging Plate
 - Screwing Kit
 - Quick Start Guide
- Qty/CTN: 10 pcs
- N.W/PCS: 1.95 kg
- G.W/CTN: 24.09 kg
- Giftbox Size: 365 x 195 x 105 mm
- Carton Size: 752 x 535 x 216 mm

Datasheet

Instruction

DNAKE S617 provides an integrated security solution. It enables user to open the door by facial recognition with liveness detection, IC & ID card and PIN Code. It also makes an easy video call with indoor monitor and mobile APP, to achieve a convenient and secure life.

Key Features

- 8-inch IPS LCD capacitive touch screen
- 3 output relays for door locks
- 120° wide-angle 2MP HD camera with automatic lighting
- Support WDR technology to lighten the dark areas and darken the overexposed parts of the image
- Support 20,000 users, 20,000 faces, and 60,000 cards
- Tamper alarm

Physical

- System: Android
- RAM: 2 GB
- ROM: 8 GB
- Front Panel: Aluminum
- Power Supply: PoE+ (802.3at) or DC 12V/3A
- Standby Power: 8 W
- Rated Power: 16 W
- Camera: 2MP, CMOS, WDR
- IR Sensor: Support
- Wiegand Port: Support
- Ethernet Port: 1 x RJ45, 10/100 Mbps adaptive
- Door Entry: Face, IC (13.56MHz) & ID (125kHz) card, PIN code, Bluetooth
- MIFARE Plus SL1/SL3 Card: Support
- Reset Button: 1
- RS485 Port: 1
- Relay Out: 3
- Input: 4
- IP / IK Rating: IP65 / IK08
- Installation: Flush Mounting
- Flush Mounting DIM: 140 x 300 x 60.3 mm
- Working Temperature: -40°C to +55°C
- Storage Temperature: -40°C to +70°C
- Working Humidity: 10% to 90% (non-condensing)

DNAKE S617

(Flush Mounting)



Datasheet

Display

- Display: 8-inch IPS LCD
- Resolution: 1280 x 800

Audio

- Audio Codec: G.711
- Echo Cancellation
- DTMF: RFC2833
- Microphone: Built-in microphone
- Speaker: 8Ω / 1W

Video

- Video Codec: H.264
- Video Resolution: up to 1920 x 1080
- Viewing Angle: 120°(H) / 75°(V) / 131°(D)
- Max. Image Transfer Rate: 1080p – 25fps
- Light Compensation: LED white light

Networking

- Protocol: ONVIF, SIP, UDP, TCP, RTP, RTSP, NTP, DNS, HTTP, DHCP, IPV4, ARP, ICMP

Package Features

- Package Content:
 - DNAKE S615
(Power adapter not included)
 - Flush Mounting Box
 - Hanging Plate
 - Screwing Kit
 - Quick Start Guide
- Qty/CTN: 10 pcs
- N.W/PCS: 2.35 kg
- G.W/CTN: 28.11 kg
- Giftbox Size: 365 x 195 x 105 mm
- Carton Size: 752 x 535 x 216 mm