

Datasheet

DNAKE TWK01



Instruction

Embrace security with a simple touch. DNAKE 2-WIRE Intercom kit is a complete solution that includes a door station, an indoor monitor, and accessories to mount. The new 2-WIRE intercom kit is immediately ready for use. Improve your safety at home while increasing convenience with DNAKE 2-WIRE Intercom Kit!

Key Features

- Plug & Play
- Indoor Monitor with WiFi
- IK07 & IP65
- Multiple Unlock methods (IC card (13.56MHz), Temp Key, QR Code, APP, Indoor monitor)
- Check alarm notifications on the APP
- CCTV integration
- Extendable to 1 Door stations, 3 indoor Monitors

Package Features

- Package Content:
 - E217W-2 (KIT) + S212-2 (KIT)
 - Brackets: 2 pcs (indoor monitor and door station)
 - Screwing Kit
 - User Manual
- Qty/CTN: 9 Pcs
- N.W/PCS: 1.75 kg
- G.W/CTN: 16.45 kg
- Giftbox Size: 280 x 268 x 65 mm
- Carton Size: 625 x 300 x 290 mm




Datasheet

DNAKE E217W-2 (KIT)

Key Features

- Easy configuration
- 7-inch TFT capacitive touch screen
- Support WiFi
- CCTV integration
- TF Card Slot



Physical

- Front Panel: Plastic
- System: Linux
- Power Supply: DC 24V
- Standby Power: 5 W
- Rated Power: 9.5 W
- Wi-Fi: IEEE802.11 b/g/n,@2.4GHz
- TF Card Slot: 1 X 32G maximum
- Relay Output: 1
- Doorbell Input: 1
- Installation: Surface Mounting
- Dimension: 195 x 130 x 17.6 mm
- Working Temperature: -40°C to +55°C
- Storage Temperature: -40°C to +70°C
- Working Humidity: 10% to 90% (non-condensing)

Display

- Display: 7-inch TFT LCD
- Screen: Capacitive touch screen
- Resolution: 1024 x 600

Audio

- Audio Codec: G.711
- Echo Cancellation
- Microphone: Built-in microphone
- Speaker: Built-in speaker

Video

- Video Codec: H.264



Datasheet

DNAKE S212-2 (KIT)

Key Features

- Single call button with name plate
- Wide-angle 2MP HD camera
- Support IC Card (13.56MHz), Temp Key, QR Code
- 2 Lock Control (1 relay out, 1 electronic lock)
- Tamper alarm



Physical

- System: Linux
- RAM: 64 MB
- ROM: 128 MB
- Front Panel: Aluminum
- Power Supply: Powered by Indoor Monitor
- Standby Power: 3.5 W
- Rated Power: 12 W
- Camera: 2MP, CMOS
- Indicator Light: 3
- Door Entry: IC Card (13.56MHz), Temp Key, QR Code
- Lock Control: 2 (1 relay out, 1 electronic lock)
- Exit Button
- Reset Button: 1
- IP / IK Rating: IP65 / IK07
- Multiple Installations: Surface Mounting(Default Bracket), Flush Mounting(Optional)
- Surface Mounting DIM:
 - Bracket: 168 x 88 x 34 mm
 - Aluminum Rain Hood (RH10): 173.5 x 94 x 53 mm
 - Aluminum Rain Hood (RH11): 174 x 94 x 66 mm
 - Stainless Rain Hood (RH14): 173 x 89 x 64.5 mm
 - Stainless Rain Hood (RH01): 179 x 92.8 x 50.5 mm
- Flush Mounting DIM: 120 × 210 × 48 mm
- Working Temperature: -40°C to +55°C
- Storage Temperature: -40°C to +70°C
- Working Humidity: 10% to 90% (non-condensing)



Datasheet

Audio

- Audio Codec: G.711
- Echo Cancellation
- DTMF: RFC2833
- Microphone: Built-in microphone
- Speaker: Built-in speaker

Networking

- Protocol: ONVIF, SIP, UDP, TCP, RTP, RTSP, NTP, DNS, HTTP, DHCP, IPV4, ARP, ICMP

Video

- Video Codec: H.264
- Video Resolution: 1280 x 720
- Viewing Angle: 110° (H) / 60° (V) / 125° (D)
- Max. Image Transfer Rate: 720p – 25fps
- Light Compensation: LED white light

