


# IP Outdoor Station

## 280SD-C5

Comparing with 902 Android intercom system, 280 Linux intercom system is more cost-effective. It offers multiple functions, including video intercom, door access, emergency call, security alarm, and property management, etc. It also supports communication with IP phone or SIP softphone, etc. via SIP protocol, and can be used with home automation and lift control system.



### Specifications:

Physical Property	
System	Linux
CPU	1GHz, ARM Cortex-A7
SDRAM	128MB
Flash	64M DDR2
Product Size	160x99.5x47(mm)
Build-in Box size	151x94x45(mm)
Treppanning Size	153x96x50(mm)
Power	DC12V/POE
Standby power	1.5W
Rated Power	3W
RFID Card Reader	IC/ID (Optional), 20,000 pcs
Button	Single Mechanical/Touch(optional)
Temperature	-40°C - +70°C
Humidity	20%-93%
IP Class	IP65
Installation	Flush Mounted

### Audio & Video

Audio Codec	G.711
Video Codec	H.264
Camera	CMOS 2M pixel
Video Resolution	1280×720p
LED Night Vision	Yes

### Network

Ethernet	10M/100Mbps, RJ-45
Protocol	TCP/IP, SIP

### Interface

Unlock circuit	Yes
Exit Button	Yes
RS485	Yes
Door Magnetic	Yes

### Key features:

- Open the door by IC/ID card (20,000 users)
- Elevator control
- Home automation
- Standard SIP 2.0
- PoE

### Dimension & Installation:

